## INK TANK SYSTEM PRINTERS ECOTANK L15150



## UNCOMPROMISING A3 PRINT QUALITY AT UNBEATABLE PRICES.



Giving you a cost-saving A3 printer that does more for your business, Epson EcoTank L15150 has an ultra-high page yield of up to 7,500 pages in black and 6,000 pages in colour. Paired with the new EcoTank pigment ink, DURABrite ET INK delivers prints that are sharp, clear and water-resistant, even in barcode mode. Enhance your productivity as Epson Heat-Free Technology enables high speed printing with lower power consumption. Get more for less, right down to the details.





# ER VERIDITIER OF



L15150



## IT'S IN THE DETAILS.

#### **DURABrite ET INK**

Get printouts that are sharp, clear and water-resistant with the new EcoTank pigment ink.

Low-Cost Productivity Enjoy ultra-high page yields of up to 7,500 (black) and 6,000 (colour) to increase your productivity.

Epson

Connect

Heat-Free Technology Achieve high speed printing at lower power consumption with Epson Heat-Free Technology.

### **SPECIFICATIONS** ECOTANK L15150

MODEL NUMBER	L15150
Printer Type Printing	Print, Scan, Copy, Fax with ADF
Printing	Drasians Cave M Dristhand
Printing Technology	PrecisonCore™ Printhead
Nozzle Configuration	800 x 1 nozzles Black, 256 x 1 nozzles per colour (Cyan, Magenta, Yellow)
Print Direction Maximum Resolution	Bi-directional printing 4800 x 2400 dpi
Minimum Ink Droplet Volume	4000 X 2400 dpi 3.8 pl
Print Speed"	5.0 pi
Draft Text - Memo, A4 (Black*1 / Colour*2)	Up to 32.0 ppm / 22.0 ppm
ISO 24734, A4 (Black / Colour)	Simplex: Up to 25.0 ipm / 12.0 ipm   Duplex: Up to 16.0 ipm / 9.0 ipm
ISO 24734, A3 (Black / Colour)	Simplex: Up to 13.5 ipm / 6.0 ipm   Duplex: Up to 10.0 ipm / 5.0 ipm
First Page Out Time (Black / Colour), A4	Simplex: Up to 13.5 ipm / 6.0 ipm   Duplex: Up to 10.0 ipm / 5.0 i
Photo Default - 10 x 15 cm / 4 x 6" "2 #3 (Border / Borderless)	Approx. 43 sec per photo (Border) / 52 sec per photo (Borderless)
Printer Language	ESC/P-R, ESC/P Raster
Automatic 2-sided printing	Yes (Up to A3)
Copying	
Copy Speed	
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 23.0 ipm / 10.0 ipm
ISO 24735, A4 (Black / Colour), ADF	Simplex: Up to 22.5 ipm / 10.0 ipm   Duplex: Up to 15.5 ipm / 7.5 ipm
Maximum Copies from Standalone	999 copies 25 - 400%
Reduction/Enlargement	20 + 400% 600 x 600 dpi
Maximum Copy Resolution	
Maximum Copy Size	A3
Scanning	
Scanner Type	Flatbed colour image scanner
Sensor Type	CIS 1200 x 2400 dei
Optical Resolution	1200 x 2400 dpi
Maximum Scan Area	297 x 431.8 (mm)
Scanner Bit Depth	49 bit input - 04 bit output
Colour	48-bit input, 24-bit output
Grayscale	16-bit input, 8-bit output
Black & White	16-bit input, 1-bit output
Scan Speed (Flatbed / ADF)	Entering and ADE (Overlaw), I. J. 2001. (11-51)
Monochrome 200dpi	Flatbed: 5 sec   ADF (Simplex / Duplex): Up to 26.0 ipm / 11.5 ipm
Colour 200dpi	Flatbed: 10 sec   ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm
Fax Function	
Type of Fax	Walk-up Black-and-white and Colour Fax Capability
Receive Memory / Page Memory	6MB, Page memory up to 550 pages
Error Correction Mode	ITU-T T.30
FAX Speed (Data Transfer Rate)	Up to 33.6 kbps, Approx. 3 sec/page
FAX Resolution	Up to 200 x 200 dpi
Transmission Paper Size	
Flatbed	A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 11 x 17"
ADF	A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 11 x 17"
Receiving Paper Size	Half Letter, A5, B5, A4, Letter, Legal, B4, 11 x 17", A3, A3+
Speed Dial / Group Dial	Up to 200 numbers, 199 groups
Fax Features	PC Fax (Transmission/Receive), Automatic Redial, Address book, Broadcast Fax (Mono Only), Transmit
	Reservation, Polling Reception, Fax Preview, Memory reception, Fax to Email, Fax to Folder, Automatic 2-sided Fax
ADF Function	
Support Paper Thickness	64-95 g/m <sup>2</sup>
Paper Capacity	50 sheets
Card Slot / USB Host Function	
Type of Direct Printing	USB Memory
Paper Handling	
Paper Feed Method	Friction Feed
Number of Paper Trays	3 (Front 2, Rear 1)
Paper Hold Capacity	
Input Capacity	Cassette 1: 250 sheets for A4 Plain paper (80 g/m <sup>2</sup> ), 50 sheets for Premium Glossy Photo Paper
	Cassette 2: 250 sheets for A4 Plain paper (80 g/m²)
	Rear Slot: 50 sheets for A4 Plain paper (80 g/m²), 20 sheets for Premium Glossy Photo Paper
Output Capacity	125 sheets for A4 Plain paper (80 g/m <sup>2</sup> ), 20 sheets for Premium Glossy Photo Paper
Paper Size	A3, Super B (13 x 19"), Indian Legal, Letter, A4, 16K (195 x 270mm), 8K (270 x 390mm), Executive (7.25 x 10.5"),
Maniana Danas Cias	B4, B5, A5, B6, A6, 8.5 x 13", 5 x 7", 4 x 6", 8 x 10", Legal (8.5 x 14"), 16:9 wide, Envelopes: #10, DL, C6, C4
Maximum Paper Size	329 x 6000mm
Print Margin	3mm top, left, right, bottom via custom settings in printer driver
Interface	
USB Notwork	USB 2.0 Ethornat Wi Ei IEEE 202 11b/a/a Wi Ei Diract
Network Network Protocol	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD
Mobile and Cloud Printing	Encon Drint, Econo Emcil Drint, Domoto Drint, Driver, Oran to Olavel
Epson Connect	Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
	Apple AirPrint, Mopria Print Service
Other Mobile Solutions	
Control Panel	4.3" Colour LCD Touch Scroop
Control Panel LCD Screen	4.3* Colour LCD Touch Screen
Control Panel LCD Screen Printer Software	
Control Panel LCD Screen Printer Software Software Support	Epson ScanSmart
Control Panel LCD Screen Printer Software	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility	Epson ScanSmart
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications Rated Voltage	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications Rated Frequency Power Consumption	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W
Control Panel LCD Screen Printer Software Software Support Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level         PC Printing/ Plain Paper Default <sup>13</sup>	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A)
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level         PC Printing/ Plain Paper Default <sup>-3</sup> Consumables	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A) Page Yield "4 Order Code
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Voltage         Rated Voltage         Standby         Sleep         Power off         Noise Level         PC Printing/Plain Paper Default <sup>ray</sup> Consumables         Black Ink Bottle	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A) Page Yield * 7,500 008
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level         PC Printing/ Plain Paper Default <sup>ra</sup> Consumables         Black Ink Bottle         Oyan Ink Bottle	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A) Page Yield "4 008 008
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Voltage         Rated Frequency         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level         PC Printing/ Plain Paper Default <sup>ra</sup> Consumables         Black Ink Bottle         Magenta Ink Bottle         Magenta Ink Bottle	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A) Page Yield * Order Code 7,500 008 6,000 (Composite Yield) 008
Control Panel         LCD Screen         Printer Software         Software Support         Operating System Compatibility         Electrical Specifications         Rated Voltage         Rated Voltage         Rated Voltage         Standby         Sleep         Power Consumption         Operating         Standby         Sleep         Power off         Noise Level         PC Printing/ Plain Paper Default <sup>ra</sup> Consumables         Black Ink Bottle         Oyan Ink Bottle	Epson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later AC 220 - 240 V 50 - 60 Hz 19.0 W 9.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 6.7 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 47 dB(A) Page Yield "4 008 008



L15150 Dimension & Weight Weight: 20.7 kg



" Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



<sup>2</sup>When printed on Epson Premium Glossy Photo Paper

"3 Default mode in accordance with ISO7779 for MFPs

14 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2020 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing Printed April 2020